

Classes Energy Limits	Number of cells/ min/ max weight LiPo	Number of cells NiMh	Number of cells/ max weight LiFePo	Runtime	Min. boat weight/length	Motor
Eco 60Wh	2S1P/2S2P/3S1P/3S2P min.360 gr Cable min. 30mm AWG 12/3.3mm ² Hardcase allowed	7 SubC	Max 510 gr. Type 26650 Max. 6 cells (3S2P)	6 minutes	min. 1000 gr.	Open
Eco Team 3x60Wh	3x2S1P/2S2P/3S1P/3S2P min.366 gr Cable min. 30mm AWG 12/3.3mm ² Hardcase allowed	3x7 SubC	3x Max 510 gr. Type 26650 3x Max. 6 cells (3S2P)	18 minutes	min. 1000 gr. Per boat	Open
Mini Eco 21Wh	2S1P/2S2P/3S1P/3S2P min.140 gr. Cable min. 30mm AWG 16/1.3mm ²	7x2/3 AF	3 cells 18650 or 2 cells 26650	6 minutes	max. 430 mm min. 450 gr.	Open
Mini Eco Team 3x21Wh	3x2S1P/2S2P/3S1P/3S2P 3x min 140 gr. Cable min. 30mm AWG 16/1.3mm ²	3x7x2/3 AF	3x3 cells 18650 or 3x2cells 26650	18 minutes	3x 430mm 3x450 gr.	Open
Mini Mono 21Wh	2S1P/2S2P/3S1P/3S2P min.140 gr. Cable min. 30mm AWG 16/1.3mm ²	7x2/3 AF	3 cells 18650 or 2 cells 26650	6 minutes	max. 450 mm min. 450 gr.	Open
Mono I 60Wh	2S1P/2S2P/3S1P/3S2P min.360 gr Cable min. 30mm AWG 12/3.3mm ² Hardcase allowed	7 SubC	3S2P max 6 cells 26650	6 minutes	Free	Open
Mono II 120Wh	From 4S1P/4S2P upto 6S1P/6S2P min.720 gr. Hardcase allowed Cable min. 30mm AWG 12/3.3mm ²	8-14 SubC	Max. 12cells 4R6S2P type 26650	6 minutes	Free	Open
Mini Hydro 21Wh	2S1P/2S2P/3S1P/3S2P min.140 gr. Cable min. 30mm AWG 16/1.3mm ²	7x2/3 AF	3 cells 18650 or 2 cells 26650	6 minutes	max. 450 mm min. 450 gr.	Open
Hydro I 60Wh	2S1P/2S2P/3S1P/3S2P min.360 gr Cable min. 30mm AWG 12/3.3mm ² Hardcase allowed	7 SubC	3S2P max 6 cells 26650	6 minutes	Free	Open
Hydro II 120Wh	From 4S1P/4S2P upto 6S1P/6S2P min.720 gr. Hardcase allowed Cable min. 30mm AWG 12/3.3mm ²	8-14 SubC	Max. 12cells 4R6S2P type 26650	6 minutes	Free	Open
FSRE 180Wh	Max 43 Volt min. 1080gr No battery changes allowed Hardcase allowed	Max 21 SubC Battery changes allowed	Max 18 cells 26650 Battery changes allowed	15 minutes	Free	Open
MINI FSRE 42Wh	From 2S1P/2S2P upto 4S1P/4S2P min.280 gr. Cable min. 30mm AWG 16/1.3mm ² No battery changes allowed	2 packs 7x2/3 AF Battery changes allowed	2 packs of 3 cells 18650 or 2 cells 26650 Battery changes allowed	10 minutes	max 550 mm	Open
F1E	43 V 1400 gr.	30 cells any type max 43 V	24 cells max 43 V	5 minutes		Open
F3E	43 V 1400 gr.	30 cells any type max 43 V	24 cells max 43 V	5 minutes		Open

Note: The 30mm cable is to prevent battery terminal beaks, it must be directly on battery!